

## CLAIMS

What is claimed as being new and desired to be protected by LETTERS PATENT of the United States is as follows:

1. (Now First Amended) A sexual aid system for allowing a user to stimulate the upper vaginal wall without impinging on the therein contained urethra ~~therein contained urethra~~, comprising in combination:

a head portion having a bi-lobar configuration with a right lobe and a left lobe, the head portion having a tip with and a linearly configured groove formed there between with the groove running the length of the head, from the tip of the head portion and inwardly, the head having a first external diameter;

a shaft portion comprising a length having a generally solid tubular configuration having a second external diameter, with the second external diameter being smaller than the first external diameter, the shaft portion being adjacent to the head portion with the shaft having a groove running contiguous with the groove of the bi-lobar head portion and running linearly along the length of the shaft from the outermost end of the head portion to the gripping portion; and

a gripping portion having a generally solid tubular configuration with a diameter being the same as the second external diameter, the gripping portion being adjacent to the shaft portion and opposite the head portion.

2. (Now First Amended) A sexual aid system comprising:  
a head portion having a bi-lobar configuration with a right lobe and a left lobe, the head portion having a length, the head portion also having a groove running between the lobes, the groove running the length of the head portion;

a shaft portion being adjacent to the head portion; and  
a gripping portion.

3. (Cancel) A sexual aid system as described in Claim 2 wherein the head portion has a groove formed between the lobes, the head having a first external diameter.

4. (Original) A sexual aid system as described in Claim 2 wherein the shaft comprises a length having a generally solid tubular configuration having a second external diameter, the shaft having a groove running contiguous with the groove of the bi-lobar head portion.

5. (Original) A sexual aid system as described in Claim 2 wherein the gripping portion is adjacent to the shaft portion and opposite the head portion and the gripping portion further includes a flange between the shaft portion and the gripping portion.

6. (Original) A sexual aid system as described in Claim 2 wherein the shaft is curved.

7. (Original) A sexual aid system as described in Claim 2 the shaft is straight.

8. (Now First Amended) A sexual aid system as described in Claim 2 wherein the ~~Sexual~~ sexual aid is fabricated of borosilicate glass, the glass having a appreciable amount of oxide of boron to enhance the lubricity of the sexual aid system.